

Coadd™ A-6111

Adhesion Promoter

DESCRIPTION

Coadd™ A-6111 is a siloxane oligomer adhesion promoter. The product has 100% active content, and is suitable for water-borne and solvent-borne coatings, printing inks, adhesives and sealants systems. It can be used in inorganic chemistry substrates to improve adhesion with co-ordinate with binder/resin of formulations.

PHYSICAL PROPERTIES

Appearance	Colorless to pale yellow liquid
Density (g/ml)	1.07
Active content (105°C, 15mins; %)	>93

Note: These properties are only typical, and do not represent product specifications

CHARACTERISTIC AND ADVANTAGES

Coadd™ A-6111 is recommended for buildings and construction coatings, printing inks, adhesives and sealants, and industrial coatings. The product has good adhesion promoting in cement and glass substrates, also it is workable in some metal substrates. Better performance found in-situ mixing formulations.

The suggested dosage (base on the total formulation): 0.3 – 5.0%.

The above dosage is only for orientation, optimum level of dosage should be determined via laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**