

Coadd™ BP-6081

Anti-popping additive

DESCRIPTION

Coadd™ BP-6081 is a mixture of low molecular polymeric surfactant, and is suitable for various water-borne systems such as industrial, automotive and wood coatings. The product has very low foaming, and also improves the leveling properties. Can effectively prevent foam related defects during drying of 2K PU and baking coating system. Excellent compatibility and easy to incorporate into various systems.

PHYSICAL PROPERTIES

Appearance	Transparent colorless liquid
Density (g/ml)	0.85
Viscosity (25°C, mPas)	<500

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ BP-6081 is recommended for water-borne industrial, automotive and wood coatings. The product can effectively prevent popping, and improve the leveling. It can also help to adjust the film drying time, extend the open-time. No adverse effect on product stability. It can be added in either grinding or let-down stage. Separation or turbidity may occur when temperature is below 5°C, please warm up and mix well before use.

Suggested dosage (based on the total formulation):0.5-2.5%

Above dosage is only for orientation, optimum level of dosage should be determined via laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**