

## Coadd™ DF-055

Defoaming Agent

### DESCRIPTION

**Coadd™ DF-055** is a non-silicone, polymer type defoamer, and is suitable for solvent-borne and UV systems. The product has excellent compatibility, can effectively remove foaming from coating surface and in-can. It also has some leveling effect, no adverse effect on inter-layer adhesion.

### PHYSICAL PROPERTIES

Appearance	Colorless to light yellow liquid
Density (g/ml)	0.8
Active content (%)	8
Viscosity (25°C, mPas)	<500

Note: These properties are only typical, and do not represent product specifications

### APPLICATION CHARACTERISTIC AND ADVANTAGES

**Coadd™ DF-055** is recommended for UV, solvent-borne and printing inks applications. The product has excellent compatibility, and is highly effective in UPR, PU and epoxy systems. Especially good compatibility performance in epoxy systems.

Suggested dosage (based on the total formulation): 0.2 – 1%

Above dosage is only for orientation, optimum level of dosage should be determined via laboratory tests.

### SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

### DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

**\*\*Please refer to SDS for more information**