

Coadd™ DF-5200

Defoaming Agent

DESCRIPTION

Coadd™ DF-5200 is a non-silicone polymer defoaming agent. Suitable for solvent and solvent free coating systems, especially suitable in non-polar range. It has strong defoaming performance and can be used as standard defoamer for different applications.

PHYSICAL PROPEERTIES

Appearance	Light yellow liquid
Density (g/ml)	0.83
Active content (%)	20%
Flash point (°C)	66

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-5200 is universal in coating and ink applications, recommended for many applications such as industrial coating, automotive coating, wood coating and architectural coating. It is recommended to add in grinding stage, in the case of post addition, high shear force would be needed to avoid craters.

Suggested dosage (base on the total formulation): 0.05 – 0.5%. Optimum dosage should be determined via a series of laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly know and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**