

Coadd™ DF-6011

Defoaming Agent

DESCRIPTION

Coadd™ DF-6011 is a polymer type defoamer, with hydrophobic particles. This product is recommended for water-borne coating systems, especially for 2K PU systems. It gives good defoaming performance, and do not affect the re-coat performance. The product is silicone free.

PHYSICAL PROPERTIES

Appearance	Colorless to light yellow liquid
Density (g/ml)	0.88
Active content (%)	49
Viscosity (25°C, mPas)	<500

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-6011 is recommended for water-borne coatings systems with ambient curing, radiation curing applications. The product is especially effective in 2K PU systems to improve the foam inhibition performance. Also the product do not give adverse effect on transparency in clear coat applications.

Suggested dosage (based on the total formulation):

0.1 – 2.0%

Above dosage are only for orientation, optimum level of dosage should be determined via laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**