

Coadd™ DF-6017A

Defoaming Agent

DESCRIPTION

Coadd™ DF-6017A is a modified polysiloxane with hydrophobic silica particles, and is suitable for water-borne coatings and printing inks system, such as glycol pastes and pigment concentrates. Especially effective during grinding of resin-containing systems.

PHYSICAL PROPERTIES

Appearance	Colorless to light yellow liquid
Density (g/ml)	1.02
Active content (%)	100
Viscosity (mPas, 25°C)	<3000

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-6017A is recommended for grind stage of water-borne pigment concentrates and glycol pastes. The product has strong defoaming performance and storage stability, improves the handling of subsequent processing. It should be added with high shear rate to avoid defects.

Suggested dosage (base on the total formulation): 0.2 – 0.8%. Optimum level of dosage should be determined via a series of laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**