

## Coadd™ DF-6022

### Defoaming Agent

#### DESCRIPTION

**Coadd™ DF-6022** is a modified polysiloxane type defoamer, and is recommended for water-borne coatings, printing inks and adhesives applications. The product has excellent bubble bursting and micro foam elimination efficiency, while has wide pH and temperature range adaptability. It is easily dispersed in water, and also easy in handling.

#### PHYSICAL PROPERTIES

Form	Colorless to light yellow liquid
Density (g/ml)	1.02
Active content (%)	100
Viscosity (3#, 60 RPM @ 25°C)	<2000

Note: These properties are only typical, and do not represent product specifications

#### APPLICATION CHARACTERISTIC AND ADVANTAGES

**Coadd™ DF-6022** is recommended for water-borne coating, printing inks and adhesive applications, has wide range of compatibility and formulation adaptability. It has excellent bubble bursting performance and wide range pH adaptability. The product is easy to handle, and can be added in any stage of coating production. More effective in emulsified epoxy systems.

Suggested dosage base on total formulation: 0.1 – 0.5%.

The above dosage is only for orientation, optimal levels should be determined through laboratory tests.

#### SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

#### DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

**\*\*Please refer to SDS for more information**