

Coadd™ DF-6035

Defoaming Agent

DESCRIPTION

Coadd™ DF-6035 is a mixture of paraffin based mineral oils and hydrophobic components. The product contains silicone, and is suitable for water-borne high gloss emulsion and emulsion paints system. It's VOC-free, and is particularly suitable for PVC range 30-50.

PHYSICAL PROPERTIES

Form	Light milky liquid
Density (g/ml)	0.88
Active content (%)	100
Flash point (°C)	>100

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-6035 is recommended for emulsion system with high gloss, semi-gloss emulsion paints, exterior wall paints with high PVC. The product is recommended to add separately in grinding stage and let-down stage (about 2/3 in grinding stage, 1/3 in let-down stage). High shear force is needed in order to minimize negative side effects, and will not affect the effectiveness. Separation may happen during transportation and storage, please mix well before use.

Suggested dosage base on the total of solid pigments and fillers formulation: 0.1 – 0.5%.

Optimal levels are determined through laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**