

Coadd™ DF-6066

Defoamer

DESCRIPTION

Coadd™ DF-6066 is a modified silicone defoaming agent for solvent-borne or solvent free coatings. It has very fast foaming destroying rate and effective in 2-pack coating systems : epoxy and polyurethane, especially in the thin coating application with balance efficiency and compatibility.

PHYSICAL PROPERTIES

Appearance	Clear to light yellowish liquid
Density (g/ml)	0.9
Non-volatile content (%)	0.8
Flash point(°C)	84

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-6066 is recommended in print inks, solvent-borne and solvent free coatings. The applications containing architectural coatings, industrial coatings, wood and furniture coatings, automotive coatings and other protective coatings. To achieve better defoaming, the defoamer should be added to the millbase. If used in the let-down procedure, sufficient shear forces must be ensured to achieve good distribution and to prevent crater formation.

The suggested dosage is typically 0.1 – 1.0% based on the total formulation, and optimal dosage levels are determined through series of tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and

safe. For your reference, the above information is only for commonly know and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**