

Coadd™ DF-6088

Defoaming Agent

DESCRIPTION

Coadd™ DF-6088 is a solution of modified polysiloxane, and is suitable for solvent-borne and solvent-free coating systems. It has high defoaming efficiency, while maintaining good compatibility during various application methods, such as spray coat and roller coat. The product also provides good transparency.

PHYSICAL PROPERTIES

Appearance	Colorless to light yellow liquid
Density (g/ml)	0.83
Active content	15%
Viscosity(25℃,mPas)	<500

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-6088 is recommended for solvent-borne and solvent-free architectural, industrial, wood coating, coil coating, ambient curing plastics and adhesives. It provides good defoaming performance, while maintaining high compatibility. The product is recommended to be added in grinding stage, if added during let-down stage, sufficient shear force is required.

Suggested dosage (base on the total formulation): 0.1 – 2%.

Optimum level of dosage should be determined via laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**