

## **Coadd™ DF-6121**

### **Defoaming Agent**

#### **DESCRIPTION**

**Coadd™ DF-6121** is a solution of non-silicone modified polyolefin polymer. It is suitable for epoxy, polyurethane and unsaturated polyester resin systems. The product has good performance in defoaming and air releasing with good compatibility.

#### **PHYSICAL PROPERTIES**

Form	Clear to light yellow liquid
Density (g/ml)	0.86
Active content (%)	44
Flash point (°C)	66

Note: These properties are only typical, and do not represent product specifications

#### **APPLICATION CHARACTERISTIC AND ADVANTAGES**

**Coadd™ DF-6121** is recommended for casting, gel coating, epoxy resins and unsaturated polyester resin systems. Can be used in coatings and composites. The product is suitable for almost all processing techniques and have high performance in air release. The product is recommended to be added in the resin and stir-mix thoroughly before adding other components.

Suggested dosage base on the total of solid pigments and fillers formulation: 0.1 – 0.5%.

Optimal levels are determined through laboratory tests.

#### **SAFETY NOTICE**

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

#### **DISCLAIMER**

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

**\*\*Please refer to SDS for more information**