

## Coadd™ DF-6139

Defoaming Agent

### DESCRIPTION

**Coadd™ DF-6139** is a metal soap-based defoamer with excellent compatibility and high defoaming efficiency. This product has excellent bubble bursting and foam inhibition performance, and can effectively eliminate micro-foams on the paint film surface. It is compatible with various water-borne resin systems, ensuring excellent defoaming efficiency while maintaining good compatibility. Particularly suitable for applications in acrylic emulsions, architectural wall emulsion paints, waterproof mortars, papermaking, and other systems.

### PHYSICAL PROPERTIES

Appearance	Light yellow liquid
Density (g/ml)	0.88
Active content (%)	100
Viscosity (25°C, mPas)	<2000

Note: These properties are only typical, and do not represent product specifications

### APPLICATION CHARACTERISTIC AND ADVANTAGES

**Coadd™ DF-6139** is recommended for various water-borne systems, especially acrylic emulsion system, architecture emulsion paints and water-proof mortars. Product has strong foam-inhibition performance, excellent bubble bursting speed, and excellent compatibility. This product can be added in any stage during painting production. Sedimentation may occur, please mix well before use.

Suggested dosage (base on the total formulation): 0.1 – 1.0%

Above dosage is only for orientation, optimum level of dosage should be determined via laboratory tests.

### SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

### DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

**\*\*Please refer to SDS for more information**