

## Coadd™ DF-6202

Defoaming Agent

### DESCRIPTION

**Coadd™ DF-6202** is a high-performance polymer type defoamer, and is suitable for water-borne industrial, printing inks and colorant applications. The product has excellent foam inhibition and foam breaking properties, and also excellent compatibility. It also has some leveling performance and water-solubility, will not cause oil flotation in low viscosity systems. The product can be diluted with water before incorporation.

### PHYSICAL PROPERTIES

Appearance	Colorless to light yellow liquid
Density (g/ml)	1.01
Active content (%)	100
Viscosity (25°C, mPas)	<2000

Note: These properties are only typical, and do not represent product specifications

### APPLICATION CHARACTERISTIC AND ADVANTAGES

**Coadd™ DF-6202** is recommended for water-borne industrial, printing inks and colorant applications. It has excellent foam inhibition and foam breaking performance in low viscosity systems. Also has good compatibility with different systems.

Suggested dosage (base on the total formulation): 0.2 – 5.0%

Above dosage is only for orientation, optimum level of dosage should be determined via laboratory tests.

### SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

### DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

**\*\*Please refer to SDS for more information**