

Coadd™ DF-6588

Defoaming Agent

DESCRIPTION

Coadd[™] **DF-6588** is a modified polyether siloxane polymer emulsion. It can as a universal defoaming agent for all kinds of water-borne coating and inks applications. This product has excellent foam-inhibition property, with long-lasting effect. It is universally suitable for different water-borne formulations with excellent compatibility. It is recommended to be used in clear coatings and pigmented systems.

PHYSICAL PROPEERTIES

Appearance	Milky white liquid
Density (g/ml)	1.0
Active content (%)	25

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd[™] **DF-6588** is recommended for water-borne architecture, industrial, wood coatings and printing inks. Especially recommended for roller coating and gravure printing applications. The product gives excellent foam-inhibition properties with long effect. It is recommended to add in let-down stage with moderate shear rate. Not recommended to be diluted by organic solvents.

Suggested dosage (based on the total formulation): 0.1 - 1.0%

Above dosage are only for orientation, optimum level of dosage should be determined via laboratory tests.

Transportation and storage suggested at 5-45 $^\circ\!\mathrm{C}$, avoid freezing.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

**Please refer to SDS for more information