

Coadd™ DF-6860

Silicone Defoamer

DESCRIPTION

Coadd™ DF-6860 is a VOC free and 100% active modified polysiloxane polymer which as defoaming agent for aqueous thick coating systems with high viscosity and high solids. It shows strong foam destroying properties in thick rolling coating applications and stucco architecture formulations. It also effective in UV coating formulations and solvent free epoxy flooring coating systems.

PHYSICAL PROPERTIES

Appearance	Translucent Liquid
Density (g/ml)	1.0
Active content (%)	100
Viscosity (mPa.S)	<8000

Note: These properties are only typical, and do not represent product specifications

APPLICATIONS

- Aqueous Building and Construction Coatings
- Solvent free UV Coatings
- Floor Coatings

CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-6860 provides strong foam destroying performance in high viscosity coating system. Please first check the compatibility in the formulations, and it maybe leads to pinhole and shrinkage.

The suggested dosage (base on the total weight of formulations): 0.05-0.5wt%.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from

practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly know and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**