

Coadd™ DF-6901

Defoaming Agent

DESCRIPTION

Coadd[™] **DF-6901** is a modified organosilicon defoamer containing hydrophobic particles, offering excellent defoaming and antifoaming properties. The product provides a balanced defoaming effect and compatibility across various resin systems while also offering certain leveling performance. It is suitable for both clear varnish and pigmented coatings formulations. The product is compatible with a wide range of temperatures and pH levels, and is easy to handle.

PHYSICAL PROPEERTIES

Appearance	Colorless to light yellow liquid
Density (g/ml)	1.0
Active content (%)	100
Viscosity (25°C, mPas)	<3000

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd[™] **DF-6901** is recommended for water-borne coatings systems such as wood and metal coatings. It can be used during both the grinding and tinting stages, and exhibits the following outstanding performance:

- High defoaming efficiency
- Excellent foam inhibition
- Exceptional micro-foam control

Suggested dosage (based on the total formulation): 0.1 - 0.6%

Above dosage are only for orientation, optimum level of dosage should be determined via laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

**Please refer to SDS for more information