

Coadd™ DF-6904

Defoaming Agent

DESCRIPTION

Coadd™ DF-6904 is a defoaming agent of modified polysiloxane with hydrophobic particles. The product has excellent bubble bursting and air-releasing performance, and possess good balance in defoaming ability and compatibility in a variety of resin systems. It is suitable for both color painting and clear coating, easy to handle and durable in wide temperature and pH range.

PHYSICAL PROPERTIES

Appearance	Light yellow cloudy liquid
Density (g/ml)	0.99
Active content (%)	100
Flash point (°C)	>100

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-6904 is recommended in water-borne wood and furniture coating, metal and flooring coating systems, can be added in both grinding and let-down stage. The product has strong foaming eliminating effect, please ensure stirring well and the product dispersing well in the formulation. Maybe has influence on clarity in varnish formulation, please check before use.

The product has the performance:

- High efficiency
- Process foaming inhibition
- Micro-foam elimination
- Good resins compatibility

Suggested dosage (base on the total formulation): 0.1 – 0.8%. Optimum level of dosage should be examined via a series of laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly know and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**