

## Coadd™ DF-8600

Defoaming Agent

### DESCRIPTION

**Coadd™ DF-8600** is a modified silicone polymer-based defoamer. It features high defoaming efficiency, excellent compatibility, and balanced foam suppression performance. It is suitable for solvent-based and solvent-free coatings, inks, and adhesive systems. Additionally, it delivers outstanding defoaming and leveling effects in composite material systems.

### PHYSICAL PROPERTIES

Appearance	Colorless to light yellow liquid
Density (g/ml)	0.9
Active content (%)	100
Viscosity (25°C, mPas)	<1000

Note: These properties are only typical, and do not represent product specifications

### APPLICATION CHARACTERISTIC AND ADVANTAGES

**Coadd™ DF-8600** is suitable for solvent-based and solvent-free coatings in architectural, industrial, wood, and automotive applications. It is also applicable to printing inks, adhesives, and composite materials. The product is recommended for addition during the grinding stage. If added during the let-down stage, high shear-rate dispersion is required. Suggested dosage (based on the total formulation): 0.1 – 0.6%

Above dosage are only for orientation, optimum level of dosage should be determined via laboratory tests.

### SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

### DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

**\*\*Please refer to SDS for more information**