

Coadd™ DF-8969

Defoaming Agent

DESCRIPTION

Coadd™ DF-8969 is a polyolefin type defoamer, and is suitable for solvent-free, wood coating and industrial coatings with radiation-curing, printing inks and adhesives. It can be used for both pigmented and unpigmented system. It is polymer type, silicone-free.

PHYSICAL PROPERTIES

Appearance	Colorless transparent liquid
Density (g/ml)	0.85
Active content (%)	100
Viscosity (25°C, mPas)	<2000

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-8969 is recommended for industrial and wood coatings, printing inks and adhesives. Especially effective for foam inhibition in PU based adhesives. The product has high defoaming efficiency, and the performance is not affected by the pigments, fillers, matting agent and any other additives in the formulation. The product should be added during grinding stage with high shear force, to prevent any defects.

Suggested dosage (base on the total formulation): 0.1 – 0.7%

Above dosage are only for orientation, optimum level of dosage should be determined via laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**