

## Coadd™ FL-2600

### Surface Additive

#### DESCRIPTION

**Coadd™ FL-2600** is a solution of hydroxy-functional polydimethylsiloxane with polyester modified groups. It is suitable to be used in solvent-borne systems with strong reduction of surface tension. The product contains silicone and OH functional groups to improve the performance.

#### PHYSICAL PROPERTIES

Form	Light yellow liquid
Density (g/ml)	1.06
Active content (%)	25
Flash point (°C)	>100

Note: These properties are only typical, and do not represent product specifications

#### APPLICATION CHARACTERISTIC AND ADVANTAGES

**Coadd™ FL-2600** is recommended for two-pack polyurethane systems, in applications such as wood & furniture coating, leather coating and etc. The functional groups will be kept at the surface of coating and react to form a polymer network, which improves the chemical resistance, surface slip and avoid dust to attach to the surface. This product also improves substrate wetting and leveling performance.

Suggested dosage base on the total of solid pigments and fillers formulation: 0.2% - 0.8%.  
Optimal levels are determined through laboratory tests.

#### SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

#### DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

**\*\*Please refer to SDS for more information**