

Coadd™ FL-6333

Surface Additive

DESCRIPTION

Coadd™ FL-6333 is a liquid-silicone type high performance surface additive, it has excellent surface leveling agent with strong reduction of surface tension. The product can be used in all aqueous, solvent-borne, solvent free systems in coatings and inks applications. The additive prevent the formation of Benard cell, and it increase slip and improve substrate wetting and anti-blocking properties.

PHYSICAL PROPEERTIES

| | |
|-------------------------|--------------------------------|
| Appearance | Colorless to light grey liquid |
| Density (g/ml) | 1.0 |
| Active content (%) | 100 |
| Viscosity (mPa.s, 25°C) | <500 |

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ FL-6333 is recommended for wood coating, industrial coating, automotive coatings, printing inks in solvent/aqueous/solvent-free formulations. It showed excellent compatibility and universal in all kinds of aqueous resins with leveling, slip and gloss improvement.

Suggested dosage (base on the total formulation): 0.05 – 1%. Optimum level of dosage should be determined via laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly know and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**