

Coadd™ FL-6630

Leveling Agent

DESCRIPTION

Coadd™ FL-6630 is a polyether modified polysiloxane type leveling agent, and is suitable for water-borne coatings such as industrial coating, as well as printing ink systems. The product has small molecular weight, and can rapidly migrate to the coating surface, lowering the surface tension. This provides excellent surface leveling and reduce cratering. The product has good water solubility, do not affect re-coat and film transparency.

PHYSICAL PROPEERTIES

| | |
|------------------------|-------------------------|
| Appearance | Semi-transparent liquid |
| Density (g/ml) | 1.02 |
| Active content (%) | 100 |
| Viscosity (25°C, mPas) | <1500 |

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ FL-6630 is recommended for water-borne coating and printing ink systems. The product can effectively improve the surface flatness, improve the gloss performance, while do not affect the transparency. Also the product has easy application.

Suggested dosage (based on the total formulation): 0.2 – 0.8%

Above dosage is only for orientation, optimum level of dosage should be determined via laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**