

Coadd™ FL-6650

Leveling Agent

DESCRIPTION

Coadd™ FL-6650 is a polymer-based surface leveling agent with excellent surface leveling performance, capable of improve the film build properties. It generates very low foam and has good defoaming properties, ensuring foam destabilization. It exhibits outstanding compatibility with acrylic systems without affecting inter-layer adhesion. The product is water-dilutable, and particularly suitable for water-borne metallic coatings and wood coatings.

PHYSICAL PROPEERTIES

Appearance	Light yellow to yellow liquid
Density (g/ml)	1.04
Active content (%)	65
Viscosity (25°C, mPas)	<15000

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ FL-6650 offers excellent wetting and leveling properties, making it suitable for use in waterborne wood coatings, industrial coatings, and certain solvent-based coatings. It demonstrates the following outstanding performance:

- Enhances the film build
- Very low foaming with defoaming properties
- Excellent leveling performance

Suggested dosage (base on the total formulation):0.2-1.0%

Above dosage are only for orientation, optimum level of dosage should be determined via laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**