

Coadd™ FL-6672

Leveling Agent

DESCRIPTION

Coadd™ FL-6672 is a water-soluble modified polyacrylate polymer solution, and is suitable for water-borne metal and wood coatings. The product strongly improves the film leveling, achieve high gloss and reduce defects of film surface. It can also provide good long-wave leveling effect, without affect the inter-layer adhesion.

PHYSICAL PROPEERTIES

Appearance	Light yellow to amber liquid
Density (g/ml)	1.03
Active content (%)	56
Viscosity (25°C, mPas)	<3500

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ FL-6672 is recommended for waterborne wood coating and industrial coatings. The product has excellent compatibility, good transparency and no fogging effect with most resins. It is recommended to add the product at the end of production stage. The viscosity of the product will be increased at low temperature, please dilute it with water or solvent (such as: BCS, BUTYL CARBITOL, DPM) for better mobility.

Suggested dosage (based on total formulation): 0.5 – 3.0%

Above dosage are only for orientation, optimum level of dosage should be determined via laboratory tests.

Suggested storage at 0-45°C. Freezing may occur at low temperature, please warm up to good flowable before use. Freezing will not affect the product performance.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from

practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**