

Coadd™ W-6010

Wetting Agent

DESCRIPTION

Coadd™ W-6010 is a 100% modified polysiloxane wetting agent, and is recommended for water-borne systems that requires substrate wetting. The product has excellent substrate wetting effect, and good compatibility. Can effectively avoid cratering, with strong diffusion effect. Also the product will not affect the coating transparency.

PHYSICAL PROPEERTIES

| | |
|------------------------|------------------------------------|
| Appearance | Colorless to semi-colorless liquid |
| Density (g/ml) | 1.0 |
| Active content (%) | 100 |
| Viscosity (25°C, mPas) | <200 |

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ W-6010 is strong reduce surface tension and recommended for water-borne clear coat and color coat systems, such as coatings, printing inks, textile and adhesive applications. The product has excellent wetting and substrate penetration performance, and good compatibility with most waterborne resins. It also helps reduce cratering formation.

Suggested dosage (base on the total formulation): 0.1 – 0.5%

Above dosage are only for orientation, optimum level of dosage should be determined via laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**