

Coadd™ W-6011

Wetting Agent

DESCRIPTION

Coadd™ W-6011 is a modified polysiloxane substrate wetting agent. It is suitable for water-borne coatings and printing inks systems. The product has strong substrate wetting efficiency, with low foaming level and does not stabilize foam. It also has strong penetration into substrates. Excellent system compatibility, can be diluted with water, and will not affect the film transparency.

PHYSICAL PROPERTIES

Appearance	Colorless to light yellow liquid
Density (g/ml)	0.95
Active content (%)	100
Viscosity (mPa.s, 25°C)	<500
Surface Tension (0.1%, mN/m)	21

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ W-6011 is recommended for water-borne general industrial, wood and furniture, building and construction, plastic and paper coatings. It also can be used in printing inks. The product is foam suppressing, and helps for surface levelling.

Suggested dosage (based on the total formulation): 0.1-1.0%. Optimum dosage should be determined via laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**