

Coadd™ W-6031

Wetting Agent

DESCRIPTION

Coadd™ W-6031 is a non-ionic wetting agent with a defoaming effect, and is suitable for various water-borne coating systems. This product has excellent substrate wetting properties, without affecting re-coat properties. Also is widely compatible for water-borne applications.

PHYSICAL PROPERTIES

Appearance	Transparent to semi-transparent liquid
Density (g/ml)	0.93
Flash point (°C)	74
Viscosity (mPa.s, 25°C)	<500

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ W-6031 is recommended for automotive coatings, industrial coatings, and printing inks. Also recommended for varnish. The product has properties such as fast wetting of substrate, and less foaming. Also do not affect the re-coat properties in water-borne systems. It can be added in both grinding and let-down stage, and can be added directly or diluted into the coating system.

Suggested dosage (base on the total formulation): 0.1 – 1.0%. Optimum level of dosage should be determined via laboratory tests.

The product may have separation and freeze under cold temperature. Warm up and mix well before use.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**