

Coadd™ W-6170

Wetting Agent

DESCRIPTION

Coadd™ W-6170 is 100% polyether modified polysiloxane substrate. It has strong surface tension reduction ability, and can be used in all kinds of water-borne coating systems for substrate wetting improvement. It can also be used in solvent-borne coating systems. The product has excellent anti-cratering performance, and improve surface leveling, with low foaming.

PHYSICAL PROPEERTIES

Appearance	Colorless to light yellow liquid
Density (g/ml)	0.97
Active content (%)	100
Viscosity (25℃, mPas)	<300

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ W-6170 is recommended for water-borne architecture, wood, industrial and auto coatings. The product has excellent compatibility, can improves gloss and leveling performance, reduce coating defects.

Suggested dosage (base on the total formulation): 0.15-1.0%.

The above recommended dosage is only for orientation, optimal level of dosage should be determined via laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**