

Coadd™ W-6770

Wetting Agent

DESCRIPTION

Coadd™ W-6770 is a solution of anionic surfactant, and is suitable for water-borne systems. The product has excellent wetting performance, with low surface tension. It can effectively reduce the system surface tension, and improve the substrate penetration and absorption.

PHYSICAL PROPERTIES

Appearance	Colorless to light yellow liquid
Density (g/ml)	1.1
Active content (%)	70
Viscosity (25°C, mPas)	<500

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ W-6770 is recommended for water-borne systems as substrate wetting agent. The product can effectively reduce the surface tension, and can rapidly migrate to interface. Also improves the system stability and durability. It also provides good emulsifying and dispersing properties. Can be used in various water-borne systems which require substrate wetting.

Suggested dosage (based on total formulation): 0.5 - 5.0%

Above dosage is only for orientation, optimum level of dosage should be determined via laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**